ACRYLOC® EXTENDA™

PRODUCT TYPE	PACKAGING	NOMINAL WEIGHT
Additives	2L Plastic Bottle	2kg

DESCRIPTION

Acryloc *Extenda* is a water-based additive designed to increase working time of acrylic based products while not affecting the characteristics or durability of the cured finish.

Acryloc *Extenda* may be added to nominated water based acrylic products, as specified in the relevant Tech Data Sheets, in order to extend working time. This may be necessary to help maintain a 'wet' edge or to assist with self-levelling of paint on smooth substrates.

FEATURES & BENEFITS

- Extends working time
- Aids workability
- Water based
- Cost effective

APPLICATION

Method - Add Acryloc *Extenda* to the product as per table below;

Product	Addition Rate
Star Point	100-120mL per 10L pail
Acryloc Texture Coats	150-200mL per 15L pail
Roofcote CRC®	up to 600mL per 20L pail
Roofcote Supa Cool®	up to 450mL per 15L pail
Court Cote™	up to 450mL per 15L pail
Weatherblock®	up to 30mL per Litre
Thermablock®	up to 30mL per Litre
Ultra Range	up to 30mL per Litre
Premium Tradeline Range	up to 30mL per Litre

- Add Acryloc *Extenda* to the product and mix thoroughly with a broad, flat stirrer, using an upward lifting action; alternatively use a power mixer
- Refer to the relevant Tech Data Sheet for full instructions on use of the individual Acryloc product.

Important Notes

- Use of Acryloc *Extenda* does NOT override maximum temperature limits for use of the particular product.
- Add Acryloc *Extenda* and mix just prior to applying the product.
- Overuse can adversely affect curing, adhesion and durability of the coating system and will void the warranty
- Not to be used with other products

Clean-Up

Clean up with water

OTHER CONSIDERATIONS

Shelf-Life – Unopened Containers

Maximum two (2) years from date of manufacture when stored correctly

Transport & Storage

Store in a cool place, upright, out of direct sunlight and above 4°C

For further information refer to **SDS** for Acryloc *Extenda*

The information provided herein is considered correct at the time of publication. It is the responsibility of those using this information to check that it is current prior to specifying or using any of the products or coating systems. Any advice, recommendation or information provided by any of the officers of Acryloc Building Products in relation to goods manufactured by it for their use and application, is given in good faith and is believed by Acryloc Building Products to be appropriate and reliable. However, this advice, recommendation and information is provided without liability or responsibility without excluding or limiting responsibility under relevant Government acts. Acryloc and other marks followed by the symbol ® or ™ are trademarks.

AUSTRALIAN OWNED, AUSTRALIAN MADE AND PROUD OF IT

TECHNICAL DATA

APPEARANCE	Clear liquid
ODOUR	Low
SPECIFIC GRAVITY (NOMINAL)	~1.03
SOLVENT FOR CLEANING	Water
FLAMMABILITY	Non-flammable

SAFETY & HANDLING

Refer to **SDS** before use. For further information on Material Safety Data Sheets, call the Acryloc **Tech – Info line** on **1300 661 745** or visit **www.acryloc.com.au**

When working with the product observe the usual precautions for handling acrylic water-based products including:

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

Full pails are HEAVY. Wear protective footwear and seek assistance if necessary

FIRST AID MEASURES

Refer to **SDS** before use. For further information on Material Safety Data Sheets, call the Acryloc **Tech – Info line** on **1300 661 745** or visit **www.acryloc.com.au**

Ingestion

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

Eye

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

Advice to Doctor

Treat symptomatically

MANUFACTURED BY:

Bizfine Pty Ltd

T/A Acryloc Building Products
174 Cavan Rd
DRY CREEK
South Australia 5094

P: +61 8 8368 0222 or 1300 661 745

E: sales@acryloc.com.au
W: www.acryloc.com.au

The information provided herein is considered correct at the time of publication. It is the responsibility of those using this information to check that it is current prior to specifying or using any of the products or coating systems. Any advice, recommendation or information provided by any of the officers of Acryloc Building Products in relation to goods manufactured by it for their use and application, is given in good faith and is believed by Acryloc Building Products to be appropriate and reliable. However, this advice, recommendation and information is provided without liability or responsibility without excluding or limiting responsibility under relevant Government acts. Acryloc and other marks followed by the symbol ® or ™ are trademarks.

AUSTRALIAN OWNED, AUSTRALIAN MADE AND PROUD OF IT